

- ALL-IN-ONE
- MOBILITY
- MODULAR
- PANELS PC
- PRINTERS**
- DISPLAYS
- ACCESSORIES

# TRP 100 III

thermal receipt printer



## Low-power thermal receipt printer

The TRP 100 III from AURES features a low-power motherboard (Energy Star certified); It switches automatically to standby mode less than a second after it stops working, ensuring average power savings of at least 30% – and thus embodying the values and requirements of Green Technologies.

The TRP 100 III can hold paper rolls up to 80mm in diameter. It features an ESC/POS compatible driver and easy paper drop in, delivering high printout quality.

The printer is available with a native USB type B port and a removable DB25 serial interface. Wifi, Ethernet and parallel ports are also available as optional extras.

The TRP 100 III offers excellent value for money and caters for a wide range of POS applications.

It is fully compatible with Windows 10.



\*([www.eu-energystar.org/fr/index.html](http://www.eu-energystar.org/fr/index.html))



# TRP 100 III



PRINTERS

Low-power motherboard (automatic standby mode enables 30% less power use on average)

Energy Star certified

Easy paper drop in

Thermal roll diameter: 80mm

200 mm/sec

ESC/POS compatible

2D barcode supported

Ready to use: all cables supplied, as well as power supply.

Easier configuration via utility software



MODEL	TRP 100 III
Printing method	Direct thermal
Printing speed	200 mm/sec
Printing width	max 72 mm / 512 dots
Resolution:	180 dpi x 180 dpi
Characters/line	Font A (12x24): 42 columns Font B (9x24): 56 columns
Paper loading	Easy paper drop in
Motherboard	Low-power Automatic standby mode (uses 30% less power)

PAPIER THERMAL	
Width:	50mm-82.5mm
Thickness	0.06-0.09mm
Max. roll diameter	83mm

CHARACTERS	
Alphanumeric characters	95
Extended graphics	128 x 18 page (1 space/page)
International characters	14
Barcodes	UPC-A, UPC-E, EAN-8, Code 39, Code 93, Code 128, ITF, Codabar, 2D: PDF 417, QR Code
Emulation	ESC/POS* compatible
Sensors	end of paper, paper low sensor, cover open sensor
Drawer port	1 double port (for 2 cash drawers)
Interfaces	Native USB (type B) + removable DB25 serial port
Interfaces (optional)	Parallel, Ethernet 10/100T and WIFI (802.11b) in option
Drivers	Windows Driver (7, XP, 2000, 2003, Vista, XP Embedded), Linux, OPOS, WEPOS, Java POS

PAPER CUTTER	
Auto cutter	MTBF 1.5 million – guillotine type
Cutting method	Total or partial cut

VARIOUS	
Power supply	External 24V - supplied
Dimensions (LxDxH)	152 x 202 x 150 mm
Weight (including paper cutter)	1.7kg
Colours	black or beige

Specifications are subject to change without notice - © AURES 2018