



ALL-IN-ONE



MOBILITY



KIOSK



PANELS PC



PRINTERS



DISPLAYS



ACCESSORIES

LC POS

universal multi-configuration
integrated system



Robust, compact EPOS system

LC POS is a robust and compact hardware, developed to suit the many applications of the POS vertical sectors at the best possible TCO.

It is a fanless, flexible and high-performance equipment available in a 4/3 format (15" screen) and equipped with a shock- and scratch-proof, multi-touch, projected, capacitive screen (10 points PCAP technology).

The hardware features a 64 GB SSD and stands up to dirt in the toughest settings (fat, crumbs, dust, splashes and leftovers in kitchens, restaurants and bakeries. It integrates an energy efficient processor (and a heat-dissipating aluminium structure, ensuring compliance with environmental standards (low carbon footprint).

LC is an accessible product whose many features (technology, ergonomics, flexibility and design) make it good value for money. It constitutes a sensible, cost-effective and long-term investment for any POS IT equipment.



LC POS



Compact, heavy duty but stylish EPOS terminal
Celeron 3965U fanless
64 GB SSD
Projected, capacitive, multi-touch screen (PCAP)
4/3 format (15")
4 GB RAM memory
Tilting base: 0-90°
Discreet yet easily accessible connectivity
Mini DP output for 2nd screen
Associated peripherals available



MODEL LC POS

Processor(s)	Celeron 3965U fanless
RAM	DDR4 SODIMM 4 GB as standard
SSD	SSD M2 64 GB
LCD	15" eDP 250 nits 50K A grade LED back-lighting
Touchscreen	Flat, zero bezel & multi-touch screen with projected, capacitive panel (PCAP)

INPUT-OUTPUT PORTS

Serial	4 serial ports (+ optional 5/12 V power supply for COM3 / COM4)
USB	5 USB 2.0 ports + 1 USB 3.0 port
LAN	10/100/1000Base-T
2nd Screen	Port with support for HDMI, DVI and VGA (mini Display Port)
Cash Drawer	24/12 V DC
Audio Power Supply	Internal loudspeaker, headphones, micro jack plug + external 19 V DC
Mini-PCI Express	1 Mini PCI Express slot (WIFI)

MISCELLANEOUS

EMI	CE, LVD, FCC Class A
Security	LVD, external adaptor UL c/us, CE, TUV, etc.
Operating Temperature	0-40 °C
Front	Dust- and splash-proof
Colour	Black
Materials	Polycarbonate (cover) + aluminium (structure)
Dimensions (W x D x H)	360.1 x 171.5 x 316.1 mm (15" - 4/3 format)
Weight	10 - 11 kg
Compatible OS	Windows 10 Enterprise, Windows 8 Industry, Windows 7 Pro, POS Ready 7, Linux, Android

OPTIONAL EXTRAS

Customer display, MSR reader, 10" second screen, 2D barcode scanner, Dallas key and Addimat readers, WI FI.